

# 400 SERIES





















## Component list

The LOC-A-BLOC System of engineered decorative walls, has a full range of structural components, all with matching face finishes.

For technical details, please either consult the LOC-A-BLOC design manual, view our website on [www.locabloc.com.au](http://www.locabloc.com.au) or discuss your specific needs with a Company representative by phoning 1800 027 070.

Some components are not available in all ranges.

COMPONENTS			
Component Part Number	Diagram (Not to Scale)	Description	Approx Weight (Kg)
400 SSS		Single side bolstered standard component 400 x 200 x 200 mm. 12.5 units / square face metre.	25
405 HSS		Single side bolstered standard half block component. 200 x 200 x 200 mm	15
400 CSS		Single side bolstered corner component. Front and one end bolstered. 400 x 200 x 200 mm.	26
400 SDS		Double side bolstered standard component. 400 x 200 x 200 mm. 12.5 units / square face metre.	30
405 HDS		Double side bolstered half component. 200 x 200 x 200 mm.	17
400 CUD		Double side bolstered universal corner component. 400 x 200 x 200 mm.	26
400 CIS		Single side bolstered internal corner component. 400 x 200 x 200 mm.	24
400 EDS		Double side bolstered component. 400 x 200 x 200 mm.	30
405 HDE		Double side bolstered standard half end component. 200 x 200 x 200 mm.	18

Component Part Number	Diagram (Not to Scale)	Description	Approx Weight (Kg)
400 SNF		Standard blank component without facing. 400 x 200 x 200 mm.	24
405 HNF		Standard blank half component without facing 200 x 200 x 200 mm.	12
400 NSV		Bolstered veneer used to match Loc-A-Bloc structures with existing walls. 400 x 200 x 35 mm.	3
400 SPB		Pier block bolstered on all four sides. 400 x 400 x 200 mm.	60
400 SPC		Standard pyramid cap for use with the pier block. 460 x 460 x 35/90 mm.	22
480 SBC		Single bolstered edge capping. 600 x 235 x 80 mm.	23
480 DBC		Double bolstered edge capping. 600 x 235 x 80 mm.	20
480 SRC		Single rounded edge capping. 600 x 280 x 80 mm.	22
480 DRC		Double rounded edge capping. 600 x 280 x 80 mm.	22

## COLOURS:

LOC-A-BLOC system products are manufactured to simulate natural materials and are generally available in a mixture of light and dark sandstone blend. Please note that some variation may occur between batches.

## PACKING:

Series 400 standard blocks are packed 60 per pallet.  
Other components are packed in varying quantities - depending on size.

## DELIVERY:

A delivery charge will be negotiated at time of order placement, cost will vary depending on quantity and location.

A repackaging fee will be charged for all entered/picked orders that are changed (By the Customer / Contractor) within 2 working days of the agreed dispatch date. The actual dispatch date may also vary and these variations will be advised at the time of the change.

## ADDITIONAL PRODUCTS:

LOC-A-BLOC can also supply other products such as Block Sealer, Anti Graffiti, and Packers.